

# MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 1 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01


SECTION 1. IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF THE COMPANY/UNDERTAKING		
1.1.	Identification of substance or mixture	
	Trade name:	HIDROFOB ELASTIC 2K
	Chemical name:	Not applicable
	Synonyms:	Not applicable
	Catalogue number:	Not applicable
1.2.	Relevant identified uses of the substance or mixture and uses advised against	
	Application:	It is used for hydro-isolation of balconies, bathrooms, basins for technical water etc. which should be lined in ceramics afterwards. For detailed information, see product data sheet/label.
	Applications not recommended:	All other applications not listed on label or product data sheet.
	Reasons for non-application:	Bad product quality of used product.
1.3.	Details of supplier of the safety data sheet	
	Company name:	Colorit d.o.o.
	Address:	Blagoja Parovića 114b
	Telephone:	+387(0)51/388-830
	Fax:	+387(0)51/388-840
	e-mail address of the person liable for MSDS:	colorit@inecco.net
	Authorized person in RS:	Colorit d.o.o., Blagoja Parovića 114b, Banja Luka
1.4.	Emergency telephone number	
	Emergency telephone number:	121 (before 112 gets activated)
	Telephone number for medical information:	124 (0-24h)
	Other information:	+381 11 360 84 40 (Poison Control Center Military Medical Academy Belgrade, Serbia)
SECTION 2. HAZARD IDENTIFICATION		
2.1.	Classification of the substance or mixture	
2.1.1.	CLP/GHS system classification	
	Hazard class and category mark:	Warning on danger (H, EUH)*:
	Skin irritat. 2	H315
	Skin sensitiveness. 1	H317
	Eye dam. 1	H318
	STOT SE 3	H335
2.1.2.	Additional information	

# MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 2 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

Not applicable	
*Full text R, H and EUH marks in Section 16.	
2.2. Label elements	
Labeling in line with:	CLP/GHS system <input checked="" type="checkbox"/> DSD/DPD system <input type="checkbox"/>
Pictogram / hazard symbol:	
Warning / danger sign and written warning:	Danger
Hazard statements (H) / Risk sign (R):	H315 – Causes skin irritation. H317 – May cause an allergic skin reaction. H318 – Causes serious eye damage. H335 – May cause respiratory irritation.
Precautionary statements (P) / Safety sign (S):	P102 – Keep out of reach of children P280 - Wear protective gloves/protective clothing/eye protection/ face protection P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P304+P340-IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER or doctor/physician. P333-P313-If skin irritation or rash occurs: Get medical advice/ attention. P501 – Dispose of contents /container in accordance with local/ national/regional/international regulations.
Supplemental hazard information:	Not applicable

2.3. Other hazards	
Product reacts alkali in contact with water.	

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3. Information on mixture ingredients				
Name	CAS number / EC number / Index number	REACH registration number	mass or volume % or range	CLP/GHS system classification*
Quartz sand	Not applicable	Excluded	45-50	Not classified

# MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 3 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

Portland cement clinker	65997-15-1/ 266-043-4/ No information	Excluded	17-22	Skin irrit. 2, H315 Skin sensit. 1, H317 Eye dam. 1, H318 STOT SE 3, H335
Mixture 5-Chloro-2-methyl-2H-isothiazol-3-one (CAS 26172-55-4) and 2-methyl-2H-isothiazol-3-one (CAS 2682-20-4)	55965-84-9/ Not applicable/ 613-167-00-5	Not applicable	0.00075	Acute tox.3, H301 Acute tox.3, H311 Corr. to skin 1B, H314 Skin sensit. 1, H317 Acute toxicity 3, H331 Acute water tox.1, H400 Chronic water tox.1,H410 M-factor 10

\* Full text R, H and EUH marks in Section 16.

## SECTION 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

	General:	In contact with doctor, bring this Material Safety Data Sheet.
	After inhalation:	Take person out on fresh air. Clear throat, drink water in order to rinse throat, blow nose to remove dust. If symptoms persist, ask for medical help. In case of inhaling larger amount, ask for urgent medical help.
	After skin contact:	Remove contaminated clothes and footwear, rinse contaminated body parts with water for about 10-15 minutes. If symptoms persist, ask for medical help.
	After eye contact:	Do not scrub eyes to avoid eye damage. Wash hands, open eyelids using clean fingers and rinse each eye with warm water thoroughly for at least 15 minutes to clear all particles. If possible, wash with saline solution. Consult ophthalmologist.
	After swallowing:	Do not induce vomiting. If conscious, rinse mouth with water and spit. Ask immediate medical help.
	Personal protection of person providing first aid:	Not applicable

### 4.2. Most important symptoms and effects, both acute and delayed

	After inhalation:	Coughing, sneezing, chest pain, throat spasm and breathing difficulties may occur.
	After skin contacts:	Skin redness, prickle, itching and skin cracking. In case of longer contact or contact with wet product could cause extreme sensitiveness, dermatitis or burns in touch with wet skin.
	After ye contact:	Could cause redness, tearing, irritation, eye pain, blurred vision and unrecoverable eye damages.
	After swallowing:	Could cause nausea, vomiting, diarrhea and abdominal pain if swallowed in bigger amount.

### 4.3. Indication of any immediate medical attention and special treatment needed

	No information available.
--	---------------------------

# MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 4 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

<b>SECTION 5. FIREFIGHTING MEASURES</b>		
5.1.	Extinguishing media	
	Suitable extinguishing agents:	Carbon-dioxide, extinguishing powder, foam or water spray. Use agents depending on surrounding subjects caught by fire.
	Inappropriate extinguishing agents:	Not applicable
5.2.	Special hazards arising from substance or mixture	
	Dangerous combustion products:	Not known.
5.3.	Advice for firefighters	
	Use breathing mask in case of unknown combustion products occurrence.	
<b>SECTION 6. ACCIDENTAL RELEASE MEASURES</b>		
6.1.	Personal precautions, protective equipment and emergency procedures	
6.1.1.	For people not trained for the accident:	
	Protective equipment:	Protective equipment as in Section 8.2.
	Accident prevention procedures:	Do not make dust. Prevent expansion into air, vacuum cleaning. Wet clearance, wet dust, sweep wet product and remove with shovel. Let it sit for 30-90 minutes and send for taking care of. In case of accident, ensure location; evacuate staff not included in sanitation.
	Emergency procedures:	Not applicable.
6.1.2.	For people participating in accident response:	
	In case vacuum and wet cleaning are not possible, ensure that workers who are clearing the product wear protective equipment as in Section 8.	
6.2.	Environmental precautions	
	Do not allow to enter sewerage, manholes and other water courses.	
6.3.	Methods and materials for containment and cleaning up	
6.3.1.	For confinement:	No information available.
6.3.2.	For cleaning up:	Pursuant to Section 6.1.1.
6.3.3.	Other information:	Avoid inhalation and skin contact.
6.4.	Reference to other Sections	
	Contaminated material should be disposed pursuant to Section 13. Use personal protection equipment pursuant to Section 8.	
<b>SECTION 7. HANDLING AND STORAGE</b>		
7.1.	Precautions for safe handling	
7.1.1.	Protective measures	

## MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 5 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

Recommendations for safe handling:	Pursuant to Section 8
Fire prevention measures:	No information available.
Aerosol and dust formation preventive measures:	Do not sweep or brush. Vacuum cleaning to avoid product dust.
Incompatible materials handling:	No information available.
Environment protective measures:	Keep bags firmly closed in horizontal position in waterproof, dry and rooms safe from contamination. Prevent disposal to water courses, sewage and manholes.

7.1.2.	General hygienic measures advice:	Do not eat, drink or smoke while using the product. Wash hands after work. Take off contaminated clothes and protective equipment before entering the room for eating.
--------	-----------------------------------	--

7.2.	Conditions for safe storage, including any incompatibilities
------	--

Technical measures and storage conditions:	Dry, ventilated room protected from humidity.
Packaging materials:	Natron paper bag.
Requests for storage rooms and containers:	Protect from humidity. Keep bags firmly closed in horizontal position in waterproof, dry and rooms safe from contamination. Keep in ventilated room. Prevent dust creation.
Storage class:	Not relevant
Other information on storage conditions:	Recommended temperature 5-25°C. Ensure good ventilation.

7.3.	Specific end use(s)
------	---------------------

Recommendations:	No information available.
Special solutions for industrial sector:	No information available.

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1.	Control parameters:
------	---------------------

Substance	CAS number	Exposure limiting value (ELV/KELV)		Biological limiting values
		ppm	mg/m <sup>3</sup>	
Portland cement dust	65997-15-1	Not applicable	10(U)* 4(R)**	No information available.

\*total dust  
\*\*respiratory dust

Substance:	No information available for substance in Section 3.
------------	--

EC no.:	Not applicable	CAS no.:	Not applicable	Not applicable
---------	----------------	----------	----------------	----------------

<b>DNEL</b>
<b>Worker</b>

# MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 6 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

Exposure way:	Acute local effects	Acute systematic effects	Chronic local effects	Chronic systematic effects
Oral	Not applicable	Not applicable	Not applicable	Not applicable
Inhalation	Not applicable	Not applicable	Not applicable	Not applicable
Skin	Not applicable	Not applicable	Not applicable	Not applicable

Key physical parameters: melting point, flammability, corrosion: Not applicable

### User

Exposure way:	Acute local effects	Acute systematic effects	Chronic local effects	Chronic systematic effects
Oral	Not applicable	Not applicable	Not applicable	Not applicable
Inhalation	Not applicable	Not applicable	Not applicable	Not applicable
Skin	Not applicable	Not applicable	Not applicable	Not applicable

### PNEC

Environment segment	PNEC
Fresh water	Not applicable
Fresh water sediments	Not applicable
Sea water	Not applicable
Sea sediments	Not applicable
Food chain	Not applicable
Microorganisms in waste water treatment	Not applicable
Land (agricultural)	Not applicable
Air	Not applicable

### 8.2. Exposure controls

#### 8.2.1. Appropriate technical control

Exposure control measures in identified application:	Avoid kneeling in the vicinity of wet product in application. If necessary, wear protective equipment as in Section 8. Do not smoke, drink or eat during work in order to avoid skin or mouth contact.
Structural measures for exposure prevention:	Pursuant to Section 7.
Organizational measures for exposure prevention:	As soon as the work is done, take off contaminated clothes and footwear, remove jewelry and watches and have a shower.
Technical measures for exposure prevention:	Pursuant to Section 7.

#### 8.2.2. Personal protective equipment

8.2.2.1 Eyes and face protection: Protective goggles should fit eyes/face well.

8.2.2.2 Skin protection:

## MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 7 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

	Hands protection:	Protective gloves made of alkali proof material.
	Protection of other body parts:	Protective long sleeve working clothes and appropriate closed footwear. Prevent wet product enter shoes.
8.2.2.3	Protection of breathing parts:	It is not necessary in case of appropriate ventilation. In case of insufficient ventilation or creation of dust, use protective filter half-mask for protection from particles.
8.2.2.4	Protection from thermal hazards:	Not applicable
8.2.3.	Environment exposure control	
	Preventive measures for substance/mixture exposure:	Pursuant to Section 6.
	Exposure control measures in identified application:	Pursuant to Section 6.
	Structural measures for exposure prevention:	Pursuant to Section 6.
	Organizational measures for exposure prevention:	Pursuant to Section 6.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

		Value	Method
	Form:	A+B comp. - fluid	Not applicable
	Color:	"A" comp.-Grey "B" comp.-White	Not applicable
	Odor:	Odourless	Not applicable
	Odor threshold:	No information available	Not applicable
	pH:	Not applicable	Not applicable
	Melting point/Freezing point:	No information available	Not applicable
	Ignition boiling point and boiling range:	No information available	Not applicable
	Ignition point:	No information available	Not applicable
	Evaporation rate:	No information available	Not applicable
	Flammability (solid, gas):	No information available	Not applicable
	Upper/lower flammability or explosion limit:	No information available	Not applicable
	Vapor pressure:	No information	

## MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 8 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

	available	Not applicable
Vapor density:	No information available	Not applicable
Relative density:	No information available	Not applicable
Pouring density:	No information available	Not applicable
Solubility:	No information available	Not applicable
Partition coefficient: n-octanol /water (log Pow):	No information available	Not applicable
Self-ignition temperature:	No information available	Not applicable
Decomposition temperature:	No information available	Not applicable
Explosion features:	No information available	Not applicable

<b>9.2.</b>	<b>Other information</b>		
	Adhesion strength in normal conditions:	≥ 0,5 N/mm <sup>2</sup>	EN 14891:2012
	Adhesion strength after immersing in water:	≥ 0,5 N/mm <sup>2</sup>	EN 14891:2012
	Adhesion strength after thermal exposure:	≥ 0,5 N/mm <sup>2</sup>	EN 14891:2012
	Adhesion strength after a cycle of freezing-unfreezing:	≥ 0,5 N/mm <sup>2</sup>	EN 14891:2012
	Water impemeability:	≥ 0,5 N/mm <sup>2</sup>	EN 14891:2012

### SECTION 10. STABILITY AND REACTIVITY

10.1.	Reactivity:	No information available.
10.2.	Chemical stability:	Stabile under normal conditions.
10.3.	Possibility of hazardous reactions:	Not applicable
10.4.	Conditions to avoid:	Temperatures under +5°C and over +25°C. Humidity in storage can cause worse quality of product.
10.5.	Incompatible materials:	Not applicable
10.6.	Hazardous decomposition products:	Not applicable

### SECTION 11. TOXICOLOGICAL INFORMATION

11.1.	Information on toxicological effects
	Acute toxicity: information for Portland cement





## MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 10 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

	applicable	applicable	applicable	applicable	applicable	
Sub-chronic inhalation	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Chronic to mouth	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Chronic on skin	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Chronic inhalation	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>Specific toxicity for organ target – single exposure (STOT SE):</b>						
	Specific effects			Exposed organ	Note	
Swallowing:	Not applicable			Not applicable	Not applicable	
Skin contact:	Possible skin irritation			Not applicable	Not applicable	
Inhalation:	Possible throat and respiratory tract irritation			Not applicable	Not applicable	
<b>Specific toxicity for organ target – repeated exposure (STOT RE): * information for Portland cement clinker</b>						
	Specific effects			Exposed organ	Note	
Sub-acute to mouth	Not applicable			Not applicable	Not applicable	
Sub-acute on skin*	Possible contact dermatitis			Not applicable	Not applicable	
Sub-acute inhalation*	Possible chronic obstructive pulmonary disease (COPD)			Not applicable	Not applicable	
Sub-chronic to mouth	Not applicable			Not applicable	Not applicable	
Sub-chronic on skin*	Possible contact dermatitis			Not applicable	Not applicable	
Sub-chronic inhalation*	Possible chronic obstructive pulmonary disease (COPD)			Not applicable	Not applicable	
Chronic to mouth	Not applicable			Not applicable	Not applicable	
Chronic on skin*	Possible contact dermatitis			Not applicable	Not applicable	
Chronic inhalation*	Possible chronic obstructive pulmonary disease (COPD)			Not applicable	Not applicable	
Aspiration hazards:		No danger since it is not used as aerosol				
Probable exposure ways:		Not applicable				
<b>Symptoms referring to physical, chemical and toxic features</b>						
	Swallowing:	Not applicable				
	Skin contact:	Not applicable				
	Inhalation:	Not applicable				
	Eye contact:	Not applicable				
Delayed current effects, as well as chronic effects due to short and extended exposure:					Not applicable	

## MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13"  
in line with Regulation (EC) no. 1907/2006

Page 11 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

Interaction effects:	Not applicable
Lack of certain information:	Not applicable
Information on mixture in the reference to its ingredients information:	Not applicable
Other information:	Not applicable

### SECTION 12. ECOLOGICAL INFORMATION

#### 12.1. Toxicity

Acute toxicity	Dose	Exposure time	Organism	Method	Evaluation	Note
Fish	LC <sub>50</sub>	96 hours	Not applicable	Not applicable	Not applicable	Not applicable
Crabs (Daphnia)	EC <sub>50</sub>	48 hours	Not applicable	Not applicable	Not applicable	
Algae/water plants	IC <sub>50</sub>	72 hours	Not applicable	Not applicable	Not applicable	
Other organisms	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
Chronic toxicity	Dose	Exposure time	Organism	Method	Evaluation	Note
Fish	LC <sub>50</sub>	96 hours	Not applicable	Not applicable	Not applicable	Not applicable
Crabs (Daphnia)	EC <sub>50</sub>	48 hours	Not applicable	Not applicable	Not applicable	Not applicable
Algae/water plants	IC <sub>50</sub>	72 hours	Not applicable	Not applicable	Not applicable	Not applicable
Other organisms	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

#### 12.2. Persistence and degradability

##### Abiotic degradability

	Half-degradability time	Method	Evaluation	Note
Sea water	Not applicable	Not applicable	Not applicable	Not applicable
Fresh water	Not applicable	Not applicable	Not applicable	
Air	Not applicable	Not applicable	Not applicable	
Soil	Not applicable	Not applicable	Not applicable	

##### Physical and photo-chemical elimination

Not applicable

##### Biodegradability:

% degradation	Time (days)	Method	Evaluation	Note

## MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13"  
in line with Regulation (EC) no. 1907/2006

Page 12 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

Not applicable	Not applicable	Not applicable	Not applicable	Not relevant since this is inorganic material.		
12.3. Bioaccumulative potential:						
Partition coefficient: n-octanol/water (log Pow)						
Value	Concentration	pH	°C	Method	Evaluation	Note
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Bioconcentration factor (BCF)						
Value	Organism	Method		Evaluation	Note	
Not applicable	Not applicable	Not applicable		Not applicable	Not applicable	
Chronic eco-toxicity						
Value	Dose	Exposure time	Organism	Method	Evaluation	Note
Chronic toxicity in fish	LC <sub>50</sub>	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Chronic toxicity in crabs (Daphnia)	EC <sub>50</sub>	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
12.4. Mobility in soil						
Known or anticipated partition in environment:						
Not relevant						
Surface pressure:						
Value	°C	Concentration	Method		Note	
Not applicable	Not applicable	Not applicable	Not applicable		Not applicable	
Adsorption/desorption						
Transport	A/D coefficient Henry's constant		log Pow	Evaporation	Method	Note
Soil-water	Not applicable		Not applicable	Not applicable	Not applicable	Not applicable
Water-air	Not applicable		Not applicable	Not applicable	Not applicable	Not applicable
Soil-air	Not applicable		Not applicable	Not applicable	Not applicable	Not applicable
12.5. Results of PBT and vPvB assessment						

## MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 13 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

	Not applicable
12.6.	Other adverse effects
	Not applicable
<b>SECTION 13. DISPOSAL CONSIDERATIONS</b>	
13.1.	Waste treatment methods
13.1.1.	Disposal of unused chemical/contaminated packaging: Disposal should be in line with official local and national regulations.
13.1.2.	Waste labeling according to waste catalogue: Material residues: 17 09 04 (mixed waste from construction and demolition other than those listed in 17 09 01, 17 09 02 and 17 09 03) Packaging residues: 15 01 01 (paper and cardboard packaging)
13.1.3.	Waste treatment forms: Not applicable
13.1.4.	Possibility of disposal to sewage: Do not dispose to sewage, waste waters and water courses etc.
13.1.5.	Other recommendations for disposal: Not applicable
13.1.6.	Regulations for waste management: Law on waste management ("Official Gazette of the Republic of Srpska", number 111/13 and 106/15), Rulebook on waste categories, tests and classification ("Official Gazette of the Republic of Srpska", no. 19/15).
<b>SECTION 14. TRANSPORT INFORMATION</b>	
Road transport (ADR)	
UN number:	Goods not hazardous based on this regulation
UN proper shipping name:	Not applicable
Transport hazard class:	Not applicable
Packaging group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	Not applicable
Railway transport (RID)	
UN number:	Goods not hazardous based on this regulation
UN proper shipping name:	Not applicable
Transport hazard class:	Not applicable
Packaging group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	Not applicable

## MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 14 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

Inland waterways transport (ADN)	
UN number:	Goods not hazardous based on this regulation
UN proper shipping name:	Not applicable
Transport hazard class:	Not applicable
Packaging group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	Not applicable
Seaways transport (IMDG)	
UN number:	Goods not hazardous based on this regulation
UN proper shipping name:	Not applicable
Transport hazard class:	Not applicable
Packaging group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	Not applicable
Transport in bulk according to Annex II of MARPOL73/78 and the IBC code:	Not applicable
Airways transport (ICAO-TI/IATA-DGR)	
UN number:	Goods not hazardous based on this regulation
UN proper shipping name:	Not applicable
Transport hazard class:	Not applicable
Packaging group:	Not applicable
Special precautions for user:	Not applicable
Additional information:	Not applicable
SECTION 15. REGULATORY INFORMATION	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Applicable regulations in the Republic of Srpska:	Law on chemicals (RS Off. Gaz. no. 25/09), Rulebook on classification, packaging and labeling of chemicals and certain products (RS Off. Gaz. no.50/10), Rulebook on contents of the Material Safety Data Sheet (RS Off. Gaz. no. 104/13), Law on waste management (RS Off. Gaz. no. 111/13 and 106/15), Rulebook on waste categories, tests and classification (RS Off. Gaz. no. 19/15).
Authorization and/or limitations in application	
Authorizations:	Not applicable
Limitations:	Not applicable
Substance causing concern:	Product does not contain substances causing concern.
Other applicable regulations	Not applicable

# MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 15 of 16

Trade name:	HIDROFOB ELASTIC 2K	BTL.C.13.01
Product code:	Production date: April 11, 2016	Version no: 01

Information on emissions of volatile organic compounds (VOC):	Not applicable
---	----------------

15.2. Chemical safety assessment	Chemical safety assessment is not performed.
----------------------------------	--

## SECTION 16. OTHER INFORMATION

Changes report:	Not applicable
-----------------	----------------

Abbreviations and acronyms:	Not applicable
-----------------------------	----------------

Basic literature and information sources:	Material Safety Data Sheet of raw materials, European Chemicals Agency, Report on product testing in certified laboratory
---	---

### Classification and procedures used for classification of mixture according to CLP/GHS system

Classification according to CLP/GHS system	Classification procedure
Skin irrit. 2 Skin sensitiveness. 1 Eye dam. 1 STOT SE 3	Classification procedure pursuant to procedures described in the Rulebook on classification, packaging and labeling of chemicals and certain products (RS Off. Gaz. no. 9/16)

### Relevant R, H, S and P signs (number and full text)

H	301	Toxic if swallowed.
H	311	Toxic in contact with skin.
H	314	Causes severe skin burns and eye damage.
H	315	Causes skin irritation
H	317	May cause an allergic skin reaction.
H	318	Causes serious eye damage
H	331	Toxic if inhaled.
H	335	May cause respiratory irritation
H	400	Very toxic to aquatic life.
H	410	Very toxic to aquatic life with long lasting effects.
P	102	Keep out of reach of children.
P	280	Wear protective gloves/protective clothing/eye protection/face protection.
P	302+P352	IF ON SKIN: Wash with plenty of soap and water.
P	304+P340	IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P	305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P	310	Immediately call a POISON CENTER or doctor/physician.
P	333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P	501	Dispose of contents /container in accordance with local/ national/ regional/international regulations

## MATERIAL SAFETY DATA SHEET

Pursuant to Rulebook on contents of Material Safety Data Sheet "Official Gazette of the Republic of Srpska number 104/13)  
in line with Regulation (EC) no. 1907/2006

Page 16 of 16

Trade name:	HIDROFOB ELASTIC 2K			BTL.C.13.01
Product code:	Production date:	April 11, 2016	Version no:	01

Advice for training:	Not applicable
Additional information:	Information provided in this MSDS is a result of our best current knowledge. This information should serve as guidance in application, use, storage, transport and disposal hence should not be considered as quality guarantee. Information refers to this product only and could not be used in combination with other materials and processes unless otherwise specified in the text. It is product user's responsibility to obey local legislative.